

## NYS DECLARATION OF COMPLIANCE CAT 6 MONOHULLS & MULTIHULLS

Short races close to the shoreline in protected waters, in daylight hours only and with effective rescue availability.

Boat Name:	Sail No:	
Date of Audit:  Audit form valid until 30 June next from the date of this fo whichever is the earlier. Subject to spot checks Regulation		_/
OWNER DETAILS		
Owner/s Name:		
Owner/s YA No:		
Owner/s Club:		
BOAT DETAILS		
LOA:	Displ (tonnes):	
Hull Material:	Hull Colour:	
Deck Material:	Deck Colour:	
Max Crew	Distinguishing Marks:	
Relevant (Maritime) Hull Registration Number:	_	
Relevant (Maritime) Sticker Issued Yes / No		
Equipment. I understand that this audit is carried out only Organising Authorities. An Auditor does not limit or reduce Owner/Person in Charge as defined in Special Regulations I undertake that all of the boat's equipment as specified in on the boat and continue to be in good working order for	e the complete and unlimi 1.02.1, 1.02.2, 1.02.3 and the AS Special Regulation	ted responsibility of the 2.03.1. Is 2017-2021 will remai
Signed_	Date	
EQUIPMENT AUDITOR DECLARATION  I have checked the abovementioned boat in accordance we the items listed were found to be on board, and as per the Outstanding items are detailed below.  Name of AuditorSigned	e regulations at the time a	•
OLITCT AND INC. ITEMS		
OUTSTANDING ITEMS  The equipment listed was complete except for the follow	ing items:	
Equipment Outstanding	Re-Inspected by	Date
-4b	spected by	

Signed by Owner\_\_\_\_\_

\_\_\_\_Date \_\_\_\_

Reg	Equipment	Compliant
2.03.1	Equipment functions and adequate for intended use	
2.03.2	Ballast and heavy equipment secured	
3.06.1	If carrying fuel or gas below decks then:	
(b)	(a) 2 exits, one forward of mast	
	(a) Minimum clearance 450mm for Age/Series Date 07/2010 or later	
3.07.1	Hatches/ports open outward if forward of max beam, except if < 0.071m <sup>2</sup>	
3.07.2	(a) (i) Hatches above water when heeled 90°	
	(a) (ii) non complying permitted; size <.071m <sup>2</sup>	
	(a) (iii) Kept shut while racing	
3.08.1	Cockpit strong, self draining at all angles of heel; permanent and integral	
	part of hull	
3.08.2	Cockpit essentially watertight	
3.08.3	Bilge pump outlet not connected to cockpit drain	
3.08.4	Cockpit sole at least 2% above Loaded Waterline Length.	
3.08.5	Wells - bow, lateral, central, stern, included in cockpit volume	
3.08.6	Cockpit volume complies with formula	
3.08.7	Number of cockpit drains:	
	Age/Series Date before 07/1977; 2 x 25mm	
	Age/Series Date after 07/1977; 4 x 20mm	
3.08.8	<b>Multihull</b> min. drain size after allowance for screen 20cm <sup>2</sup> per m <sup>3</sup> of cockpit	
3.12.6	Lifelines if fitted:	
If fitted	(a) Lifelines uncoated stainless steel wire	
	(b) Lifeline coating not moulded to wire	
	(d) Gap secured by lanyard 100mm or less; lanyard replaced annually	
	(e) Strength lifeline system, wire size comply	
3.14.1	Toe rail minimum height 25mm	
	Age Date before 01/1981 20mm	
3.14.2	Toe rail not required on multihulls	
3.17.2	Cooking stove/heating appliance if installed: securely fastened, accessible shutoff	
3.17.3	Gas only permitted for cooking. Methylated spirits acceptable for cooking	
3.17.4	(a) 'REMEMBER TURN OFF GAS AT BOTTLE' sign	
	(b) Gas detection system if appliance uses a pilot light	
3.17.5	Disposable gas canister to be 225gms or less	
3.17.6	Gas bottle, spare canisters in separate, ventilated, self draining locker, vapour can only escape overboard	
3.20.6	Bilge pump not to discharge into closed cockpit	
	Bilge pump not connected to cockpit drains	
3.20.7	(a) Bilge pump minimum suction bore 25mm	
	(b) Bilge pump and strum boxes accessible	
3.20.9	2 x 8 ltr buckets <b>stout</b> construction with lanyard	
3.24.6	If motor installed: Separate starter battery if no hand crank	
3.24.7	Separate generators, if carried and permanently installed:	
	covered; exhaust, fuel supply and tank also permanently installed	
3.24.8	If motor installed/carried:	
	Fuel tank shut off valve/cock(s) if fuel can escape or siphoning possible	

Signed by Owner	Date	

3.24.9	(a) Inboard petrol tanks permanently installed, metal, vented to open air,	
If motor	electrically grounded, filler position prevents fuel/vapour entering boat	
	(b) Diesel tanks metal or other certified material	
	(c) Fuel lines comply	
	(d) Outboard motor remote fuel tank and lines comply	
	(e) Petrol not below decks in portable containers	
	(f) No flexible diesel tank unless incorporating a liner	
3.24.10	If no motor and 5.5m or less; oars/paddles; blade area 0.04m <sup>2</sup>	
3.28.1	Hull identification, minimum 50mm; name, club and sail number OR name	
	and State Marine Authority rego	
4.01.1	Sail numbers as per RRS 77 and Appendix G	
4.01.2	Sail numbers; on separate cloth, eyelets and lashings	
4.02	Plugs through hull openings (SR 3.09)	
4.03.2	(a) Anchorage points, through bolted/welded deckplates/other suitable	
Clip	strong points	
Points	(b) Position to clip on/unclip from below and move between cockpit & deck	
	(c) Clipping points 2/3rds crew other than jackstays	
4.04.1	Fire extinguishers: inspection date:	
	If naked flame or auxiliary engine then 1 x 10B(E)	
	More or higher rating extinguishers maybe required depending on boat size/layout	
4.04.4	Fire blanket if cooking facilities	
4.05.1	(a) Anchor and warp sizes as per Table 2 or Table 3	
	Typekg	
	(d) Strong point for bitter end	
4.06.2	1 x flashlight water resistant, floating type, with spare batteries and bulb	
4.07.4	Medical kit, waterproof container; alternative brands permitted; contents	
	listed	
4.07.9	First aid contents as per list at end of this form	
4.10.3	AS Racing Rules of Sailing 2017-2020 except for open boats	
4.15.3	Sharp knife sheathed, restrained in or near cockpit	
4.16.1	Name on all buoyant equipment and items	
4.16.2	Personal PFD marked to identify owner	
4.17.1	Retro-reflective tape on lifebuoys, lifeslings, liferafts	
4.26	Demonstrate equipment or method by which crew may be assisted back on board	
4.27.1	V Distress sheet or International Signal carried	
5.01.1	Number of PFDs:	
5.01.2	(f) All PFDs AS4758-2015 (minimum Level 50) or AS1512-1996 Type 1 or Type 2	
	Number of PFDs Type 1:	
	Number of PFDs Type 2:	
	Number of PFDs AS 4758:	
	or equivalent or more stringent overseas standard	
	(j) If no lifelines complying with 3.12, then PFD Type 1 or 2 or AS 4758 worn	
	by each crew on deck	
	Branded with respective standard mark of approval	

Signed by Owner_	Date	

5.01.5	Inflatable PFDs, Service dates list all:	
	(x )(x )	
5.01.6	Each non inflatable PFD annual check	

4.07.9 FIRST AID CONTENTS LIST		
Soluble aspirin (eg Disprin) x 20		
Disposable gloves x 10		
Crepe bandages 75mm x 1.5m x2		
Low absorbency non-adherent dressing (eg Melolin) x 5		
Bandaids or equivalent roll of bandaid x 20		
Saline solution 30ml x 2		
Sunscreen 30+ SPF 250ml x 1		
Scissors, stainless steel x 1		
CPR mask x 1 or face shields x 6		